

# Set: 1 kV Connection Joint with 4 Pieces Bolted Connectors 332710030, 4-cores, PVC/XLPE 35-70 + 95 SE, Parking Position

This joint kit, based on DIN SPEC 47640, inclusive insulated screw connectors are suitable for connections with PVC or XLPE insulated cables for low voltage applications up to 1 kV.

It is also suitable for live working while complying with legal regulations.

$D_{AS}$  = Diameter, outer tubing

$D_{IS}$  = Diameter, inner tubing

$L_{AS}$  = Length, outer tubing

$L_{IS}$  = Length, inner tubing



*Picture may vary.*

## Technical Data

<b>Article no.</b>	<b>332 818 730</b>
<b>Number of conductor</b>	<b>4</b>
<b>Number of screw connectors</b>	<b>4</b>
<b>Conductor cross section</b>	<b>(mm<sup>2</sup>) 35 - 70 + 95 SE</b>
<b>No. LV screw connector</b>	<b>332 710 030</b>
<b>with parking position</b>	<b>yes</b>
<b>Shear bolts</b>	<b>yes</b>

## Dimensions

<b>Joint outside diameter</b>	<b><math>D_{AS}</math> Ø (mm)</b>	<b>89/17</b>
<b>Joint inside diameter</b>	<b><math>D_{IS}</math> Ø mm</b>	<b>44/7</b>
<b>Joint length</b>	<b><math>L_{AS}</math> (mm)</b>	<b>800</b>
<b>Joint inner length</b>	<b><math>L_{IS}</math> Ø mm</b>	<b>200</b>