

# Set: 1 kV Connection Joint with 4 Pieces Bolted Connectors 332710040, 4-cores, PVC/XLPE 35Cu + 50-120 + 150 SE, Parking Position

This joint kit, based on DIN SPEC 47640, inclusive insulated screw connectors are suitable for connections with PVC or XLPE insulated cables for low voltage applications up to 1 kV. It is also suitable for live working while complying with legal regulations.

$D_{AS}$  = Diameter, outer tubing

$D_{IS}$  = Diameter, inner tubing

$L_{AS}$  = Length, outer tubing

$L_{IS}$  = Length, inner tubing



*Picture may vary.*

## Technical Data

<b>Article no.</b>	<b>332 818 740</b>
<b>Number of conductor</b>	<b>4</b>
<b>Number of screw connectors</b>	<b>4</b>
<b>Conductor cross section</b>	<b>(mm<sup>2</sup>) 35 Cu + 50 - 120 + 150 SE</b>
<b>No. LV screw connector</b>	<b>332 710 040</b>
<b>with parking position</b>	<b>yes</b>
<b>Shear bolts</b>	<b>yes</b>

## Dimensions

<b>Joint outside diameter</b>	<b><math>D_{AS}</math> Ø (mm)</b>	<b>115/23</b>
<b>Joint inside diameter</b>	<b><math>D_{IS}</math> Ø mm</b>	<b>51/8</b>
<b>Joint length</b>	<b><math>L_{AS}</math> (mm)</b>	<b>960</b>
<b>Joint inner length</b>	<b><math>L_{IS}</math> Ø mm</b>	<b>244</b>