

# 1 kV Connection Joint for Bolted Connectors, 4-cores VPE/PVC 25-95 DIN SPEC 47640

Compliant to DIN SPEC 47640.

For nominal voltage  $U_0/U = 0.6/1$  kV

$D_{AS}$  = Diameter, outer tubing

$D_{IS}$  = Diameter, inner tubing

$D_H$  = Envelope circle

$L_{AS}$  = Length, outer tubing

$L_{IS}$  = Length, inner tubing



*Picture may vary.*

## Technical Data

<b>Article no.</b>	<b>333 111 213</b>
<b>Number of conductor</b>	<b>4</b>
<b>Conductor cross section</b>	(mm <sup>2</sup> ) <b>25 - 95</b>
<b>Nominal voltage</b>	$U_0 / U$ (kV) <b>0.6/1</b>
<b>with parking position</b>	<b>no</b>

## Dimensions

<b>Joint outside diameter</b>	$D_{AS}$ Ø (mm)	<b>85/25</b>
<b>Joint inside diameter</b>	$D_{IS}$ Ø mm	<b>33/8</b>
<b>Joint length</b>	$L_{AS}$ (mm)	<b>630</b>
<b>Joint inner length</b>	$L_{IS}$ Ø mm	<b>160</b>
<b>Connector envelope circle</b>	$D_H$ (mm)	<b>28</b>
<b>Connector diameter</b>	$D$ Ø (mm)	<b>25</b>
<b>Connector length</b>	(mm)	<b>55</b>