

# 1 kV Connection Joint for Bolted Connectors, 4-cores VPE/PVC 95-240 DIN SPEC 47640

Compliant to DIN SPEC 47640.

For nominal voltage  $U_0/U = 0.6/1$  kV

$D_{AS}$  = Diameter, outer tubing

$D_{IS}$  = Diameter, inner tubing

$D_H$  = Envelope circle

$L_{AS}$  = Length, outer tubing

$L_{IS}$  = Length, inner tubing



*Picture may vary.*

## Technical Data

<b>Article no.</b>	<b>333 111 215</b>
<b>Number of conductor</b>	<b>4</b>
<b>Conductor cross section</b>	<b>(mm<sup>2</sup>) 95 - 240</b>
<b>Nominal voltage</b>	<b><math>U_0 / U</math> (kV) 0.6/1</b>
<b>with parking position</b>	<b>no</b>

## Dimensions

<b>Joint outside diameter</b>	<b><math>D_{AS}</math> Ø (mm)</b>	<b>130/36</b>
<b>Joint inside diameter</b>	<b><math>D_{IS}</math> Ø mm</b>	<b>45/12</b>
<b>Joint length</b>	<b><math>L_{AS}</math> (mm)</b>	<b>950</b>
<b>Joint inner length</b>	<b><math>L_{IS}</math> Ø mm</b>	<b>260</b>
<b>Connector envelope circle</b>	<b><math>D_H</math> (mm)</b>	<b>42</b>
<b>Connector diameter</b>	<b><math>D</math> Ø (mm)</b>	<b>38</b>
<b>Connector length</b>	<b>(mm)</b>	<b>128</b>