

# 1 kV Connection Joint for Bolted and Crimp Connectors, 4-cores, VPE/PVC 25-95, Parking Position and Repair Sleeve

On the basis of DIN SPEC 47640.

$D_{AS}$  = Diameter, outer tubing

$D_{IS}$  = Diameter, inner tubing

$D_H$  = Envelope circle

$L_{AS}$  = Length, outer tubing

$L_{IS}$  = Length, inner tubing



*Picture may vary.*

## Technical Data

<b>Article no.</b>	<b>333 115 213</b>
<b>Number of conductor</b>	<b>4</b>
<b>Conductor cross section</b>	<b>(mm<sup>2</sup>) 25 - 95</b>

## Dimensions

<b>Joint outside diameter</b>	<b><math>D_{AS}</math> Ø (mm)</b>	<b>93/25</b>
<b>Joint inside diameter</b>	<b><math>D_{IS}</math> Ø mm</b>	<b>33/8</b>
<b>Joint length</b>	<b><math>L_{AS}</math> (mm)</b>	<b>1000</b>
<b>Joint inner length</b>	<b><math>L_{IS}</math> Ø mm</b>	<b>190</b>
<b>Connector envelope circle</b>	<b><math>D_H</math> (mm)</b>	<b>28</b>
<b>Connector diameter</b>	<b><math>D</math> Ø (mm)</b>	<b>25</b>
<b>Connector length</b>	<b>(mm)</b>	<b>55</b>