

# Contact wire earthing clamp P52D

This contact wire earth clamp is fitted with a rigid spindle and is used for grooved, circular or shaped conductors.

## Technical description:

- With feeler rod for easy application onto the contact wire
- The spring-mounted thrust block is connected to the M12 connecting screw on the back by means of flexible copper straps

## Material:

- Body made of cast copper, electro-tinned
- Thrust blocks and spindle of high-strength copper alloy, electro-tinned
- M12 A2 steel connecting screw
- Feeler rod made of spring steel, electro-galvanized



*Picture may vary.*

## Technical Data

<b>Article no.</b>		<b>361 499 499</b>
<b>Area of application</b>		<b>Railway Application</b>
<b>Type</b>		<b>P52D</b>
<b>Max. cross section of connected cable</b>	<b>(mm<sup>2</sup>)</b>	<b>50</b>
<b>Max. short-circuit current</b>	<b>I<sub>K</sub> 1s (kA)</b>	<b>36,5</b>
<b>Contact wire</b>	<b>(mm<sup>2</sup>)</b>	<b>Ri 80 - 150</b>
<b>Clamping width</b>	<b>(mm)</b>	<b>30</b>
<b>Weight</b>	<b>(g)</b>	<b>942</b>
<b>Remark</b>		<b>with rigid spindle</b>