

## Two-Pole Earthing and Short-Circuiting Device



Picture may vary.

### Technical Data

|  |                             |      |
|--|-----------------------------|------|
| <b>Article no.</b>                             | <b>369 100 001 00340</b>    |      |
| <b>Earthing Clamp</b>                          | crimp cable lug             |      |
| <b>Line clamp</b>                              | P3D                         |      |
| <b>Clamping range line clamp</b>               | 2 - 20                      |      |
| <b>for ball pin diameter</b>                   | Ø (mm)                      | 20   |
| <b>for T-bolt diameter</b>                     | Ø (mm)                      | 15   |
| <b>Cable cross section short-circuit cable</b> | (mm <sup>2</sup> )          | 70   |
| <b>Earthing cable cross section</b>            | (mm <sup>2</sup> )          | 70   |
| <b>Cable length a</b>                          | (m)                         | 1    |
| <b>Cable length b</b>                          | (m)                         | 1    |
| <b>Cable length c</b>                          | (m)                         | 1,5  |
| <b>Max. short-circuit current</b>              | (kA)                        | 13,8 |
| <b>Max. short-circuit current 0,5 s</b>        | (I <sub>k</sub> 0,5 s (kA)) | 19,5 |
| <b>Insulating material</b>                     | PVC transparent             |      |
| <b>Language</b>                                | German                      |      |