

# Single-Pole Earthing and Short-Circuiting Device



*Picture may vary.*

## Technical Data

|                                      |                            |
|--------------------------------------|----------------------------|
| <b>Article no.</b>                   | <b>369 201 001 03517</b>   |
| <b>Earthing Clamp</b>                | <b>U2</b>                  |
| <b>Clamping range earthing clamp</b> | <b>2 - 20</b>              |
| <b>for ball pin diameter</b>         | <b>Ø (mm) 25</b>           |
| <b>for T-bolt diameter</b>           | <b>Ø (mm) 15</b>           |
| <b>Line clamp</b>                    | <b>P5D</b>                 |
| <b>Clamping range line clamp</b>     | <b>2 - 25</b>              |
| <b>for ball pin diameter</b>         | <b>Ø (mm) 25/30</b>        |
| <b>for T-bolt diameter</b>           | <b>Ø (mm) 20</b>           |
| <b>Earthing cable cross section</b>  | <b>(mm<sup>2</sup>) 95</b> |
| <b>Cable length</b>                  | <b>(m) 3</b>               |
| <b>Max. short-circuit current</b>    | <b>(kA) 18,7</b>           |
| <b>Insulating material</b>           | <b>PVC transparent</b>     |
| <b>Language</b>                      | <b>German, English</b>     |