

# Three-Pole Earthing and Short-Circuiting Devices



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>369 203 001 04171</b>	
<b>Earthing Clamp</b>	<b>E2</b>	
<b>Clamping range earthing clamp</b>	<b>2 - 30</b>	
<b>Line clamp</b>	<b>P4D</b>	
<b>Clamping range line clamp</b>	<b>5 - 20</b>	
<b>for ball pin diameter</b>	<b>Ø (mm)</b>	<b>25</b>
<b>for T-bolt diameter</b>	<b>Ø (mm)</b>	<b>15</b>
<b>Cable cross section short-circuit cable</b>	<b>(mm<sup>2</sup>)</b>	<b>70</b>
<b>Earthing cable cross section</b>	<b>(mm<sup>2</sup>)</b>	<b>35</b>
<b>Cable length a</b>	<b>(m)</b>	<b>0,6</b>
<b>Cable length b</b>	<b>(m)</b>	<b>0,6</b>
<b>Cable length d</b>	<b>(m)</b>	<b>0,6</b>
<b>Cable length c</b>	<b>(m)</b>	<b>1,5</b>
<b>Max. short-circuit current</b>	<b>(kA)</b>	<b>13,8</b>
<b>Insulating material</b>	<b>PVC transparent</b>	
<b>Language</b>	<b>German, English</b>	