

# Three-Pole Earthing and Short-Circuiting Devices



Picture may vary.

## Technical Data

|  |                          |            |
|--|--------------------------|------------|
| <b>Article no.</b>                             | <b>369 203 001 04577</b> |            |
| <b>Earthing Clamp</b>                          | <b>HM12</b>              |            |
| <b>Line clamp</b>                              | <b>P4D</b>               |            |
| <b>Clamping range line clamp</b>               | <b>5 - 20</b>            |            |
| <b>for ball pin diameter</b>                   | <b>Ø (mm)</b>            | <b>25</b>  |
| <b>for T-bolt diameter</b>                     | <b>Ø (mm)</b>            | <b>15</b>  |
| <b>Cable cross section short-circuit cable</b> | <b>(mm<sup>2</sup>)</b>  | <b>50</b>  |
| <b>Earthing cable cross section</b>            | <b>(mm<sup>2</sup>)</b>  | <b>50</b>  |
| <b>Cable length a</b>                          | <b>(m)</b>               | <b>0,6</b> |
| <b>Cable length b</b>                          | <b>(m)</b>               | <b>0,6</b> |
| <b>Cable length d</b>                          | <b>(m)</b>               | <b>0,6</b> |
| <b>Cable length c</b>                          | <b>(m)</b>               | <b>1,2</b> |
| <b>Max. short-circuit current</b>              | <b>(kA)</b>              | <b>9,9</b> |
| <b>Insulating material</b>                     | <b>PVC transparent</b>   |            |
| <b>Language</b>                                | <b>German, English</b>   |            |