

# Three-Pole Earthing and Short-Circuiting Devices



Picture may vary.

## Technical Data

|  |                            |
|--|----------------------------|
| <b>Article no.</b>                             | <b>369 203 001 04869</b>   |
| <b>Earthing Clamp</b>                          | <b>HM12</b>                |
| <b>Line clamp</b>                              | <b>P5D</b>                 |
| <b>Clamping range line clamp</b>               | <b>5 - 30</b>              |
| <b>for ball pin diameter</b>                   | <b>Ø (mm) 25/30</b>        |
| <b>for T-bolt diameter</b>                     | <b>Ø (mm) 20</b>           |
| <b>Cable cross section short-circuit cable</b> | <b>(mm<sup>2</sup>) 95</b> |
| <b>Earthing cable cross section</b>            | <b>(mm<sup>2</sup>) 35</b> |
| <b>Cable length a</b>                          | <b>(m) 0,6</b>             |
| <b>Cable length b</b>                          | <b>(m) 0,6</b>             |
| <b>Cable length d</b>                          | <b>(m) 0,6</b>             |
| <b>Cable length c</b>                          | <b>(m) 1,8</b>             |
| <b>Max. short-circuit current</b>              | <b>(kA) 18,7</b>           |
| <b>Insulating material</b>                     | <b>PVC transparent</b>     |
| <b>Language</b>                                | <b>German, English</b>     |