

# Three-Pole Earthing and Short-Circuiting Devices



Picture may vary.

## Technical Data

|  |                          |       |
|--|--------------------------|-------|
| <b>Article no.</b>                             | <b>369 203 001 04970</b> |       |
| <b>Earthing Clamp</b>                          | HS12                     |       |
| <b>Line clamp</b>                              | P5D                      |       |
| <b>Clamping range line clamp</b>               | 5 - 30                   |       |
| <b>for ball pin diameter</b>                   | <b>Ø (mm)</b>            | 25/30 |
| <b>for T-bolt diameter</b>                     | <b>Ø (mm)</b>            | 20    |
| <b>Cable cross section short-circuit cable</b> | <b>(mm<sup>2</sup>)</b>  | 50    |
| <b>Earthing cable cross section</b>            | <b>(mm<sup>2</sup>)</b>  | 50    |
| <b>Cable length a</b>                          | <b>(m)</b>               | 0,6   |
| <b>Cable length b</b>                          | <b>(m)</b>               | 0,6   |
| <b>Cable length d</b>                          | <b>(m)</b>               | 0,6   |
| <b>Cable length c</b>                          | <b>(m)</b>               | 2     |
| <b>Max. short-circuit current</b>              | <b>(kA)</b>              | 9,9   |
| <b>Insulating material</b>                     | PVC transparent          |       |
| <b>Language</b>                                | German, English          |       |