

# Three-Pole Earthing and Short-Circuiting Devices



Picture may vary.

## Technical Data

|  |                          |             |
|--|--------------------------|-------------|
| <b>Article no.</b>                             | <b>369 203 001 05352</b> |             |
| <b>Earthing Clamp</b>                          | <b>E2</b>                |             |
| <b>Clamping range earthing clamp</b>           | <b>2 - 30</b>            |             |
| <b>Line clamp</b>                              | <b>crimp cable lug</b>   |             |
| <b>Cable cross section short-circuit cable</b> | <b>(mm<sup>2</sup>)</b>  | <b>70</b>   |
| <b>Earthing cable cross section</b>            | <b>(mm<sup>2</sup>)</b>  | <b>35</b>   |
| <b>Cable length a</b>                          | <b>(m)</b>               | <b>2</b>    |
| <b>Cable length b</b>                          | <b>(m)</b>               | <b>2,5</b>  |
| <b>Cable length d</b>                          | <b>(m)</b>               | <b>2</b>    |
| <b>Cable length c</b>                          | <b>(m)</b>               | <b>2</b>    |
| <b>Max. short-circuit current</b>              | <b>(kA)</b>              | <b>13,8</b> |
| <b>Insulating material</b>                     | <b>PVC transparent</b>   |             |
| <b>Language</b>                                | <b>German, English</b>   |             |