

# HVC8 Connector, Variant 113, with Cable, Assembled

3-pole, straight connector with one screw as locking mechanism.

Adapted to high voltage cable Radox Elastomere 35 mm<sup>2</sup> from company Huber & Suhner.

Compatible receptacle: 382 005 102 or upgrade kit (B- to C-sample) 389 015 401.

Product validation according to specification ZF AVE 130.



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>382 999 999 00025</b>
<b>Type designation</b>	<b>CC-HVC8-35_RadoxS-3-180°-A-CR-SF-SC-NI-113</b>
<b>Cable length</b>	(m) 10
<b>HVC8 Electric contact</b>	Ø (mm) 8
<b>Number of power contacts</b>	3
<b>Connection type</b>	35 mm <sup>2</sup> compressed
<b>Housing</b>	Aluminium (sea water resistant), straight
<b>Mechanical Coding</b>	A
<b>Service life</b>	60.000 / 12
<b>Contact surface</b>	silver plated copper
<b>Locking mechanism</b>	one central screw
<b>Mating cycles</b>	50
<b>Cable cross section</b>	(mm <sup>2</sup> ) 35
<b>Suitable high voltage cable</b>	100 103 509
<b>Suitable high voltage cable</b>	84100296
<b>Rated voltage</b>	(V) 900, DIN EN 60664-1, 4000m NN
<b>Electrical withstand voltage</b>	(kV DC) 2,7
<b>IP protection class DIN 40050-9</b>	IP 6K9K, IP X7, IP X6K
<b>IP protection class DIN 40050-9 not mounted</b>	IP 20

<b>Article no.</b>		<b>382 999 999 00025</b>
Screening effectiveness	(dB)	>55 dB for f = 0,1 MHz up to 100 MHz
Corrosion resistance		672 hours, ISO 16750-4, Chapter 5.5.2
Nominal current	(A)	220 (Contact)
Overload current capability	(A/0,1s @ 80° C)	4000
Overload current capability	(A/1s @ 80° C)	1400
Overload current capability	(A/5s @ 80° C)	600
Overload current capability	(A/10s @ 80° C)	450
High short circuit strength	(kA/0,1s @ 20° C)	5
Rated shield current	(A)	10
Max. shield current	(A)	50
Ambient temperature	(°C)	-30 up to +85
Lower storage temperature	(°C)	-40 (48h)
Upper storage temperature	(°C)	100 (96h)
Insertion force	(N)	< 100
Pull-off force	(N)	< 100
Side load on connector housing	(Nm)	4