

## CONNEX Connection Joint, Size 4 / 6, 72.5 kV

Special joint type with Al-housing and SF6 gas density measure.

There are consumables just for one plug-in process included in the scope of delivery.

### Application:

- Pluggable connection between two cable runs
- Electrical installation testing

### Features:

- Fast installation thanks to preassembly
- Combination of different conductor materials
- Connects a vast range of cable cross-sections
- Metal clad
- Fully insulated
- High short-circuit strength
- Maintenance-free
- Maintenance-free gas density monitor (manometer) with remote monitoring option
- Bursting disc

Sockets are covered with plastic covers. Voltage-proof dummy plugs to be ordered separately.



Picture may vary.

## Technical Data

<b>Article no.</b>		<b>827 053 131</b>
<b>Max. system voltage</b>	<b>U<sub>m</sub> (kV)</b>	<b>72,5</b>
<b>Size</b>		<b>4 / 6</b>
<b>Design</b>		<b>HV CONNEX Special Joints</b>
<b>Insulation medium</b>		<b>gas</b>
<b>Working place</b>		<b>Indoor, outdoor and offshore</b>
<b>Nominal current</b>	<b>I<sub>N</sub> (A)</b>	<b>2500</b>
<b>Applicable standards</b>		<b>IEC 60840, IEC 60137, IEC 62271-203</b>
<b>Protection Type</b>		<b>IP 67</b>

## Dimensions

<b>Length</b>	<b>(mm)</b>	<b>1137</b>
---------------	-------------	-------------