PFISTERER
Your Power Connection

CONNEX Elbow Socket, for Air, up to 17.5 kV

Application:

- Elbow Socket for air
- Insulating medium: air

Characteristics:

- Testing in factory due to short time amount for plugging the accessories
- Assembly time is significantly reduced and safe assembling guaranteed
- Touch-proof and maintenance-free
- Not offshore-proof



Picture may vary.

Technical Data

Article no.		**827 119 180**
Size		**1**
Max. system voltage	**U_m (kV)**	**17,5**
Nominal voltage	**U_n (kV)**	**15**
Conductor Earth Voltage	**U_0 (kV)**	**7,5**
Applicable standards		**EN 50180:2011**
Working place		**indoor and outdoor**
Insulation medium		**air**
Rated lightning impulse withstand voltage BIL	**(kV)**	**95**
Nominal current I_n	**(A)**	**630**
Max. dynamic short circuit current	**(kA)**	**125**

© 2026 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications

Dimensions

Pitch circle diameter for fastening	**(mm)**	**95**
Fitting length	**(mm)**	**168**
Total length	**(mm)**	**374 mm**

© 2026 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications