PFISTERER
Your Power Connection

CONNEX Elbow Socket with Compression Cable Lug, for Air, up to 17.5 kV

Application:

- Elbow Socket for air
- Insulating medium: air

Characteristics:

- Testing in factory due to short time amount for plugging the accessories
- Assembly time is significantly reduced and safe assembling guaranteed
- Touch-proof and maintenance-free
- Not offshore-proof



Picture may vary.

Technical Data

Article no.		827 119 181
Size		1
Max. system voltage	U_m (kV)	17,5
Nominal voltage	U_n (kV)	15
Conductor Earth Voltage	U_0 (kV)	8,7
Applicable standards		EN 50180:2011
Working place		indoor and outdoor
Insulation medium		air
Rated lightning impulse withstand voltage BIL	(kV)	95
Nominal current I_n	(A)	630
Max. dynamic short circuit current	(kA)	125

© 2026 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications

Dimensions

Pitch circle diameter for fastening	**(mm)**	**95**
Fitting length	**(mm)**	**168**
Total length	**(mm)**	**406 mm**

© 2026 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications