

## EURO-Test HR-System, 230VAC, 50Hz

This test device can be used to carry out function tests on continuous voltage indicators. It can also be used for the in-service test. The test device is operated on a power socket and, during the function test, simulate the minimum response threshold specified in the standard.

This EURO-Test HR tester is suitable for checking the continuous voltage indicator of HR systems.



Picture may vary.

### Technical Data

<b>Article no.</b>		<b>827 160 001</b>
<b>Min. threshold voltage</b>	<b><math>U_{tmin}</math> (V)</b>	<b>90</b>
<b>Min. threshold current range</b>	<b><math>I_{tmin}</math> (<math>\mu</math>A)</b>	<b>2,5</b>
<b>Permissible ambient temperature</b>	<b>(°C)</b>	<b>-25 ... +55</b>
<b>Standby indication</b>		<b>LED</b>
<b>Dimensions: width x height x depth</b>	<b>(mm)</b>	<b>50 x 40 x 100</b>
<b>Line voltage</b>	<b>(V AC)</b>	<b>230 VAC 50 Hz</b>

### Dimensions

<b>Height</b>	<b>(mm)</b>	<b>40</b>
<b>Width</b>	<b>(mm)</b>	<b>50</b>
<b>Depth</b>	<b>(mm)</b>	<b>100</b>