

# CONNEX Surge Arrester 10 kA



Picture may vary.

## Technical Data

<b>Article no.</b>	<b>827 513 090</b>	
<b>Size</b>		1
<b>Rated voltage <math>U_r</math></b>	$U_r$ (kV)	9
<b>Max. continuous rating <math>U_c</math></b>	$U_c$ (kV)	7
<b>Environment temperature</b>	(°C)	-25 up to +40
<b>Max. residual voltage <math>U_{res}</math> at 5 kA, 8/20 <math>\mu</math>s</b>	8/20 $\mu$ s 5 kA (kV)	24
<b>Max. residual voltage <math>U_{res}</math> at 8/20 <math>\mu</math>s 10 kA</b>	8/20 $\mu$ s 10 kA (kV)	26
<b>Max. residual voltage <math>U_{res}</math> at steep impulse 1/20 <math>\mu</math>s</b>	Steilstoß 1/20 $\mu$ s (kV)	29
<b>Line discharge class</b>		1
<b>Power consumption capacity</b>	(kJ/kV)	2
<b>Rated discharge surge current</b>	(kA)	10
<b>High peak current</b>	(kA)	65
<b>Long-wave peak current</b>	(A)	250
<b>Short-circuit withstand current</b>	(kA)	16
<b>Earth Conductor</b>	(mm <sup>2</sup> )	min. 16

## Dimensions

<b>Surge arrester length when mounted</b>	<b>L (mm)</b>	<b>350</b>
<b>Length l</b>	<b>(mm)</b>	<b>350</b>
<b>Surge arrester diameter</b>	<b>X (mm)</b>	<b>65</b>
<b>Thickness d</b>	<b>(mm)</b>	<b>66</b>
<b>Dimension x</b>	<b>(mm)</b>	<b>66</b>