

# CONNEX Socket, Size 4 for GIS, up to 72.5 kV

## Application:

- Socket for mounting into gas-insulated switchgears (GIS), gas-insulated transformers, joints and other gas-insulated equipment

## Characteristics:

- Testing of switchgear in factory due to short time amount for plugging the accessories
- Assembly time is significantly reduced and safe assembling guaranteed
- Touch-proof, maintenance-free and floodable (IP67)



Picture may vary.

## Technical Data

<b>Article no.</b>		<b>828 040 999 00025</b>
<b>Size</b>		<b>4</b>
<b>Max. system voltage</b>	<b>U<sub>m</sub> (kV)</b>	<b>72,5</b>
<b>Nominal voltage</b>	<b>U<sub>n</sub> (kV)</b>	<b>60 - 69</b>
<b>Conductor residual voltage</b>	<b>U<sub>0</sub> (kV)</b>	<b>36</b>
<b>Applicable standards</b>		<b>IEC 62271-209 (Fig.3)</b>
<b>Fitting length</b>	<b>(mm)</b>	<b>583</b>
<b>Pitch circle diameter</b>	<b>(mm)</b>	<b>270</b>
<b>Diameter of flange opening</b>	<b>(mm)</b>	<b>200</b>
<b>Capacitive voltage tap</b>		<b>without</b>
<b>Filler cast resin</b>		<b>Aluminium oxide (white)</b>
<b>Working place</b>		<b>outdoor, indoor and offshore</b>
<b>Insulation medium</b>		<b>gas</b>
<b>Routine test: AC withstand voltage 1 min.</b>	<b>(kV)</b>	<b>160</b>
<b>Routine test: Partial discharge test &lt; 2 pC at</b>	<b>(kV)</b>	<b>140</b>
<b>Rated lightning impulse withstand voltage BIL</b>	<b>(kV)</b>	<b>325</b>
<b>Nominal current</b>	<b>I<sub>N</sub> (A)</b>	<b>2500</b>
<b>Max. dynamic short circuit current</b>	<b>(kA)</b>	<b>160</b>