

CONNEX Socket, Size 7-S, for GIS, up to 362 kV

Application:

- Socket for mounting into gas-insulated switchgears (GIS), gas-insulated transformers, joints and other gas-insulated equipment

Characteristics:

- Compact design of socket allows very small cable boxes and reduction of insulation gas
- Testing of switchgear in factory due to short time amount for plugging the accessories
- Assembly time is significantly reduced and safe assembling guaranteed
- Touch-proof, maintenance-free and floodable (IP67)



Picture may vary.

Technical Data

Article no.		828 070 999 00004
Size		7-S
Max. system voltage	U_m (kV)	362
Nominal voltage	U_n (kV)	330 - 345
Conductor residual voltage	U₀ (kV)	190
Applicable standards		Compact design
Fitting length	(mm)	505
Pitch circle diameter	(mm)	395
Diameter of flange opening	(mm)	320
Capacitive voltage tap		with
Working place		outdoor, indoor and offshore
Insulation medium		gas
Routine test: AC withstand voltage 1 min.	(kV)	560
Routine test: Partial discharge test < 2 pC at	(kV)	285
Rated lightning impulse withstand voltage BIL	(kV)	1175
Nominal current	I_N (A)	4000
Max. dynamic short circuit current	(kA)	170