

CONNEX Socket, Size 8, for Transformer, up to 420 kV

Application:

- Socket for mounting into transformers and other oil-insulated equipment

Characteristics:

- Compact design of the socket allows very small cable boxes and reduction of insulation oil
- Transformer testing in factory due to short time amount for plugging the accessories
- Assembly time is significantly reduced and safe assembling guaranteed
- Touch-proof, maintenance-free and floodable (IP67)



Picture may vary.

Technical Data

| | | |
|--|---------------------------|--|
| Article no. | | 828 081 999 00001 |
| Size | | 8 |
| Max. system voltage | U_m (kV) | 420 |
| Nominal voltage | U_n (kV) | 380 - 400 |
| Conductor residual voltage | U₀ (kV) | 220 |
| Applicable standards | | Compact design |
| Fitting length | (mm) | 750 |
| Pitch circle diameter | (mm) | 640 |
| Capacitive voltage tap | | with |
| Ventilation valve | | without |
| Working place | | outdoor, indoor and offshore |
| Insulation medium | | mineral oil (variants for ester on request) |
| Routine test: AC withstand voltage 1 min. | (kV) | 650 |
| Routine test: Partial discharge test < 5 pC at | (kV) | 590 |
| Rated lightning impulse withstand voltage BIL | (kV) | 1425 |
| Nominal current | I_N (A) | 4000 |
| Max. dynamic short circuit current | (kA) | 170 |