PFISTERER

# CONNEX Separable Connector, Size 1, with Voltage Tap, up to 12 kV

**Standard article no.**

- for DIN VDE cables
- for RM-conductor (stranded circular) of aluminium or copper
- for single core cable with copper wire shield without armouring
- with sealing system (bell flange seal and shrink tubing)
- for indoor and outdoor applications
- not soil-resistant and not offshore-proof
- offshore version on request (see product configurator)
- Packaging unit: set with three separable connectors
- 3-core version on request (see product configurator)

The picture shows an MV-CONNEX separable connector with voltage tap.

*Picture may vary.*

## Technical Data

| Article no. | | 850 110 150 |
|---|---|---|
| Size | | 1 |
| Max. system voltage | $U_m$ (kV) | 12 |
| Cable specification | | DIN VDE |
| Capacitive voltage tap | | with |
| for cable cross section | ($mm^2$) | 150 |
| Insulation thickness | (mm) | 3,4 |
| for diameter over conductor | (mm) | 13,8 - 15,1 |
| for diameter over PE/VPE insulation | Ø (mm) | 20,0 - 23,5 |

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications