

Voltage Detector KP-Test 5, 10 - 12 kV

The capacitive voltage detector **KP-Test 5** can be used for medium voltage switchgears and medium voltage overhead lines. Thereby it is suitable for indoor and outdoor use. There are devices both for testing a nominal voltage and a nominal voltage range.

- Nominal voltage range: **10 - 12 kV**
- Nominal frequency: **50 Hz**
- Designed and type-tested according to **IEC 61243-1**
- Length of insulating element when assembled 520 mm

Technical description:

- Double signalling
- Integrated audible signal
- Extremely bright LEDs
- Maximum resistance to interference fields
- Self-test at switch-on
- Can be used in rain and snow
- Removeable forked electrode for overhead lines is included in the scope of delivery



Picture may vary.

Technical Data

Article no.	930 110 010 00028
Nominal voltage	U_n (kV) 10 - 12
Nominal frequency	f_N (Hz) 50
Suitable bag	A1
suitable case	K3
Voltage type	AC
Area of application	Switchgear / Overhead Line
Type of device	complete
Language on labels	de
Design	indoor and outdoor
Handle	made of ribbed solid rubber
Climate class	W, N
Contact electrode	Ring electrode with M8 internal thread
Power supply	2 x lithium batteries
Type	KP-Test 5
Type tested according to	IEC 61243-1

Dimensions

Total length	L_G (mm)	1060
Penetration depth	A_i (mm)	393
Length of handle	L_H (mm)	135
Diameter of insulating element	d (mm)	24
Length of insulating element	L_I (mm)	520