

Voltage Detector KP-Test 5A, 3.6 - 6 kV, for Capacitive Measuring Points on Outer Cone

The capacitive voltage detector **KP-Test 5A** is only usable at capacitive measuring points of outer cone's cable connectors according to DIN VDE 0278-629-1. Due to the innovative contact electrode attachment the cover caps of the voltage tap could be easily removed before testing.

- Nominal voltage range: **3.6 - 6 kV**
- Nominal frequency: **50 Hz**
- Designed and type-tested according to **IEC 61243-1**

Technical description:

- Double signalling
- Integrated audible signal
- Extremely bright LEDs
- Maximum resistance to interference fields
- Can be used in rain and snow
- Self-test at switch-on
- Removeable contact electrode attachment to pull-off the cover cap



Picture may vary.

Technical Data

Article no.	930 190 001 00639	
Nominal voltage	U_n (kV)	3.6 - 6
Nominal frequency	f_N (Hz)	50
Suitable bag	A1	
suitable case	K3	
Voltage type	AC	
Area of application	Capacitive measuring point outer cone cable connectors according to DIN VDE 0278-629-1	
Type of device	complete	
Language on labels	en	
Design	indoor and outdoor	
Handle	made of ribbed solid rubber	
Climate class	W, N	
Contact electrode	Ring electrode with M8 internal thread	
Power supply	2 x lithium batteries	
Type	KP-Test 5A	
Type tested according to	IEC 61243-1	

Dimensions

Total length	L_G (mm)	887
Penetration depth	A_i (mm)	220
Length of handle	L_H (mm)	135
Diameter of insulating element	d (mm)	24
Length of insulating element	L_I (mm)	520