

Voltage Detector KP-Test 5L, 20 - 36 kV

The **KP-Test 5L** is used at medium voltage overhead lines.

- Nominal voltage range: **20 - 36 kV**
- Nominal frequency: **50 Hz**
- Designed and type-tested according to **IEC 61243-1**
- Total device length without insulating poles: **345 mm**

Technical description:

- Double signalling
- Integrated audible signal for reliable voltage tests even in a noisy environment
- Extremely bright LEDs in clear layout to prevent confusion
- Maximum resistance to interference fields
- Self-test at switch-on
- Can be used in rain and snow
- Available in separate design

Suitable insulating poles:

- 973 501 001 with $L_o = 725$ mm
- 624 760 001 with $L_o = 1485$ mm



Picture may vary.

Technical Data

Article no.	930 210 001 00104	
Nominal voltage	U_n (kV)	20 - 36
Nominal frequency	f_N (Hz)	50
Suitable bag		A4
suitable case		K1
Voltage type		AC
Area of application		Overhead Line
Type of device		separate
Language on labels		de
Design		outdoor
Climate class		W, N
Power supply		2 x alkaline batteries
Type		KP-Test 5L
Type tested according to		IEC 61243-1

Dimensions

Total length	L _G (mm)	345
--------------	---------------------	-----
