

Voltage Detector KP-Test 5H+, 60 - 110 kV

The capacitive voltage detector **KP-Test 5H+** is used at high voltage overhead lines and high voltage outdoor substations.

- Nominal voltage range: **60 - 110 kV**
- Nominal frequency: **50 Hz**
- Designed and type-tested according to **IEC 61243-1**
- Insertion depth **A_i = 898 mm**

Technical description:

- Double signalling
- Integrated audible signal
- Extremely bright LEDs
- Maximum resistance to interference fields
- Self-test at switch-on
- Can be used in rain and snow



Picture may vary.

Technical Data

Article no.	930 250 002 00003	
Nominal voltage	U_n (kV)	60 - 110
Quantity of insulating poles		2
Nominal frequency	f_N (Hz)	50
Suitable bag		B1
Carrying bag included		no
Voltage type		AC
Area of application		Switchgear / Overhead Line
Type of device		complete
Language on labels		de
Design		indoor and outdoor
Climate class		W, N
Contact electrode		fork electrode
Power supply		2 x lithium batteries
Type		KP-Test 5H+
Type tested according to		IEC 61243-1

Dimensions

Total length	L_G (mm)	3114
Penetration depth	A_i (mm)	898
Insulating length	L_I (mm)	1317
Transporting length	L_T (mm)	1128
Diameter of insulating element	d (mm)	33