### **PFISTERER**

# Voltage Detector KP-Test 5H+, 110 - 220 kV

The capacitive voltage detector **KP-Test 5H+** is used at high voltage overhead lines and high voltage outdoor substations.

- Nominal voltage range: 110 220 kV
- Nominal frequency: **50 Hz**
- Designed and type-tested according to IEC 61243-1
- Insertion depth A<sub>i</sub> = 898 mm

#### **Technical description:**

- Double signalling
- Integrated audible signal
- Extremely bright LEDs
- Maximum resistance to interference fields
- Self-test at switch-on
- Can be used in rain and snow



Picture may vary.

#### **Technical Data**

Article no.		930 250 002 00031	
Nominal voltage	U <sub>n</sub> (kV)	110 - 220	
Nominal frequency	f <sub>N</sub> (Hz)	50	
Suitable bag		B2	
Carrying bag included		no	
Voltage type		AC	
Area of application		Switchgear / Overhead Line	
Type of device		complete	
Language on labels		fr	
Design		indoor and outdoor	
Climate class		W, N	
Contact electrode		fork electrode	
Power supply		2 x lithium batteries	
Туре		KP-Test 5H+	
Type tested according to		IEC 61243-1	

# **PFISTERER**

## **Dimensions**

Total length	L <sub>G</sub> (mm)	4354
Penetration depth	A <sub>i</sub> (mm)	898
Insulating length	L <sub>I</sub> (mm)	2317
Transporting length	L <sub>T</sub> (mm)	1720
Diameter of insulating element	d (mm)	33