

Distance Voltage Detector KP-Test 5D dual, 110 kV, with Carrying Bag

The capacitive distance voltage detector **KP-Test 5D dual** is used at high voltage overhead lines. It indicates the presence of operating voltage when applying the device to the earthed insulator protective system. A proportional acoustic warning sound, which warn the operator with a warning tone becoming faster and faster when approach live line system.

- Nominal voltage range: **110 kV**
- Nominal frequency: **16,7 Hz and 50 Hz**
- Designed and type-tested according to **DIN VDE V 0682-417**

Technical description:

- Double signalling
- Integrated audible signal
- Extremely bright LEDs
- Proportional acoustic warning sound
- Maximum resistance to interference fields
- Self-test at switch-on
- Can be used in rain and snow



Picture may vary.

Technical Data

Article no.		930 470 501 00019
Nominal voltage level I	U _n (kV)	110 kV / 16,7 Hz
Nominal voltage level II	U _n (kV)	110 kV / 50 Hz
Quantity of insulating poles		1
Suitable bag		C1
Carrying bag included		yes
Voltage type		AC
Area of application		Overhead Line
Type of device		complete
Language on labels		en
Design		outdoor
Climate class		W, N
Power supply		2 x lithium batteries
Type		KP-Test 5D dual
Type tested according to		DIN VDE V 0682-417

Dimensions

Total length	L _G (mm)	980
Penetration depth	A _i (mm)	270
Insulating length	L _i (mm)	520
Transporting length	L _T (mm)	980
Diameter of insulating element	d (mm)	24