PFISTERER

Outdoor Termination ESP170-C58, 170 kV, porcelain, oil-insulated

The self-supporting, oil-insulated ESP termination with alternating sheds made of porcelain is available for voltages up to 550 kV and with various creepage distance lengths. Porcelain is still valued today, particularly in some regions of the world, as a proven, robust material. The silicone stress cone is identical to that of the ESS.

Picture may vary.

At a glance:

- For high voltages up to 550 kV
- Available in various creepage distance lengths
- Porcelain insulator with alternating sheds
- High mechanical strength
- Stress control element made of silicone
- Routine tested before delivery
- Optional accessories: Splice box, partial discharge sensor, arcing horn, corona ring

Contact technology:

- Standard design: Head fitting with SICON shear-off bolt technology
- On request: Head fitting with compression technology
- Specially for copper enameled wires conductors: Head fitting with FrontCon technology

Technical Data

Article no.		ESP170-C58
Max. system voltage	U_m (kV)	170
Type Termination		oil insulated, porcelain insulator (ESP)
Applicable standards		IEC 60840
Rated lightning impulse withstand voltage BIL	(kV)	750
Conductor cross section	(mm^2)	185 - 2500
Diameter over cable insulation - prepared	(mm)	53.2 - 99.0
Max. diameter over outer cable sheath	(mm)	150
Minimum creepage distance	(mm)	5800
Min. arcing distance	(mm)	1995
Environment temperature	(°C)	-30 up to +55 °C

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications