


Supported Outdoor Termination EST72-C19-SUB SA, 72.5 kV, dry-insulated, with surge arrester

Cable termination and surge arrester in one

With the EST SUB SA, the surge arrester serves as a fixing point for the cable termination at the same time. No additional supporting elements are necessary. Various response voltages for the surge arrester are available.

- Quick and easy to install
- Oil- and gas-free - leak-proof
- Maintenance-free
- 100% electrically individually tested
- Proven technology



Picture may vary.

Technical Data

Article no.	EST72-C19-SUB SA	
Max. system voltage	U _m (kV)	72,5
Type Termination	dry-insulated, supported, for substations, with surge arrester (EST-SUB SA)	
Applicable standards	IEC 60840, IEC 60815	
Rated lightning impulse withstand voltage BIL	(kV)	325
Conductor cross section	(mm ²)	95 - 1200
Diameter over cable insulation - prepared	(mm)	32.5 - 64.4
Minimum creepage distance	(mm)	1813
Min. arcing distance	(mm)	906
Applied standard for the integrated surge arrester	IEC 60099	
Rated voltage U _r of the integrated surge arrester	(kV)	54 - 114 kV available in steps of 3 kV
Nominal discharge current of the integrated surge arrester	(kA)	10 or 20
Line discharge class of the integrated surge arrester	SM or SH 3 or 4	
Max. rated short circuit current of the integrated surge arrester	(kA)	63