PFISTERER

One-piece slip-on joint, MSA72-XKFR, 72.5 kV, with screen interruption with 1 concentric bonding cable

IXOSIL joints for permanent cable connections
The well proven slip-on technology permits fast installation and the secure connection of cables with extruded insulation with copper or aluminum conductors. Using the patented SICON bolted connector allows the conductor to connected with optimal contact force and without special tools.

- Fast installation
- Simple slip-on technology, proven in many years of service
- Water-resistant housing
- Combination of different conductor materials (aluminum, copper)
- Main insulation: Silicone

Picture may vary.

Technical Data

Article no.		MSA72-XKFR
Max. system voltage	U_m (kV)	72,5
Rated lightning impulse withstand voltage BIL	(kV)	325
Screen version		screen interruption with concentric bonding cable
Outer housing		shrink sleeve fiber glass reinforced
Inner housing		aluminium foil
Applicable standards		IEC 60840
Conductor cross section	(mm^2)	95 - 1600
Diameter over cable insulation - prepared	(mm)	37.0 - 87.0
Max. diameter over outer cable sheath	(mm)	120
Environment temperature	(°C)	-30 up to +55 °C

© 2024 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications