



( 1 : 10 )

- 1 Erdungspunkte: M12 (2x)  
Earth connection points: M12 (2x)
- 2 IEC Messabgriff: 2 kV  
IEC test tap: 2 kV
- 3 Schutzhaube  
Protection cap
- 4 ANSI Spannungsabgriff: 20 kV  
ANSI Voltage tap: 20 kV

Maßstab / Scale 1:5 (1:10)	Gewicht ca. / Weight ca. (kg) 250000	Produktbezeichnung / Title CONNEX Df 7 145kV 2600A RIS IEC IEEE	
Entwickelt von / Developed by Ferenci	Name / name 2016-06-01	Bauart / type of document en=2600A, Spag, ANSH-IEC, Bolzen 2"Gewinde VS	
Geprüft von / Checked by Kuna	Datum / date 2016-06-01	Bauart / type of document CONNEX Bs 7 145kV 2600A RIS IEC IEEE	
Geprüft durch / Checked by 20201892	Änderdatum / date of issue 2020-11-23	Hersteller / Manufacturer Ross	Skizzen / Drawings 05
Pfisterer Kabelaussysteme GmbH Germany		Zeichnung / Drawing SIZ-164932	
		Form / Size A1	
		Skala / Scale 1/1	
		Drawing Code 828193005A	

This reproduction, distribution or use without the written consent of the copyright holder is prohibited. Any reproduction, distribution or use without the written consent of the copyright holder is prohibited.